



PMS 150 W – Permanentmagnet Synchronous motor

Applications

- Battery powered application with Voltages from 48 V DC to 96 V DC (for traction applications; Compressors, Pumps etc.)
- Industrial applications with a DC Bus current of 320 V DC or 560 V DC (Fans; industrial machinery etc.)

Rpm	1500 min ⁻¹ to 6000 min ⁻¹	Depending on the windings, adapted to the System Voltage
Rated Power	6,0 kW to 20 kW	Depending on rpm
Peak Torque	80 Nm	Pulse-Peak torque only up to 30 % of rated rpm
Motorfeedback	Analog Hallsensors (sin/cos); Resolver or Encoders	Depending on controller-specifications
Weight	~ 23,6 kg	Incl. sin/cos Encoder, without break

Max. power at different motor-speed with watercooling at a max.temperature of 60°C , and 6 l / min of cooling-liquid flow.

Motor Speed	Rated Power	Rated Torque	Peak Torque	Efficiency
1500 min ⁻¹	6,0 kW	38,2 Nm	80 Nm	88 %
3000 min ⁻¹	12,0 kW	38,2 Nm	80 Nm	93 %
4500 min ⁻¹	16,0 kW	34,0 Nm	80 Nm	94 %
6000 min ⁻¹	20,0 kW	31,8 Nm	80 Nm	94 %

Other motor speed, torque and power ratings for customised Applications can be checked by request, as well as a direct mounting of gearings and breaks



General technical specs for the PMS 0150 W

Motortype	Permanent excited synchronous-Disc (pancake) motor
cooling	watercooling with max. 60 °C , a mx. Pressure of 3 bar and a minimum liquid-flow of 6 l / min
Operation mode	S1 (continuous)
Polpairs	4
Magnet material	Neodymium-Iron-Bor
Insulation Class	Class F according VDE 0530
Electrical strength	VDE 0530 – 2000V / 10s
Type of construction	Flange type according IM B14
Electrical connections	Plugs (mating plug not included) or wire
Protection class	IP 54
Environmental temperature	-10 °C to + 40 °C
Demagnetization temperature	> 5 x I _N
Max. Peak torque at intermittent Duty	1,5-times of rated torque for about 15 seconds
Max. pulse-torque	~2,5-times of rated torque for max. 0,5 seconds
Motorfeedback	Resolver 2-poles, Encoder or Analog Hallsensors with sin/cos output
Temperaturesensors	KTY84-130 or PTC (NAT=120°C)